









Name	Qty
 LIGHTING	
 P01	2
 P01A	18
 P01B	1
 P01C	4
 LIGHTING CONTROLS	
 nLIGHT CONTROLLER	1
 NPOD TOUCH PANEL	1

LUMINAIRE SCHEDULE

TYPE MARK	LOCATION	DESCRIPTION	MANUFACTURER	MODEL	DIMMING	CCT/CRI	DELIVERED LUMENS	WATTAGE	VOLTAGE	FINISH	NOTES
P01	SITE	POLE MOUNTED SINGLE HEAD LED FIXTURE WITH FULL CUT-OFF OPTICS. PROVIDE WITH 25' TALL SQUARE POLE TO MATCH EXISTING POLES AND COORDINATE MOUNTING ACCESSORY TYPE WITH EXISTING. CLEAR GASKETED TEMPERED GLASS LENS. TYPE IV DISTRIBUTION. IP66 RATED FOR WET LOCATIONS. PROVIDE WITH NLIGHT AIR WIRELESS CONTROLS FOR DIMMING, MOTION AND DAYLIGHT CONTROLS SUITABLE FOR 25FT HEIGHT POLE.	LITHONIA	RSX2 LED-P4 SERIES	0-10V DIMMING TO 10%	3000K	23054 lm	187 W	277 V	STANDARD TO MATCH EXISTING	PROVIDE UNIVERSAL 120-277VOLTS
P01A	SITE	SAME AS P01 EXCEPT MOUNTED TO EXISTING POLE. COORDINATE MOUNTING ACCESSORY NEEDED WITH EXISTING POLE TYPE.	LITHONIA	RSX2 LED-P4 SERIES	0-10V DIMMING TO 10%	3000K	23054 lm	187 W	277 V	STANDARD TO MATCH EXISTING	PROVIDE UNIVERSAL 120-277VOLTS
P01B	SITE	SIMILAR TO P01 EXCEPT TYPE II DISTRIBUTION.	LITHONIA	RSX2 LED-P4 SERIES	0-10V DIMMING TO 10%	3000K	22836 lm	187 W	277 V	STANDARD TO MATCH EXISTING	PROVIDE UNIVERSAL 120-277VOLTS
P01C	SITE	SIMILAR TO P01A EXCEPT TYPE II DISTRIBUTION.	LITHONIA	RSX2 LED-P4 SERIES	0-10V DIMMING TO 10%	3000K	22836 lm	187 W	277 V	STANDARD TO MATCH EXISTING	PROVIDE UNIVERSAL 120-277VOLTS

4. PROVIDE A nLIGHT ECLYPSE SYSTEM CONTROLLER
COMPATITABLE WITH nLIGHT ENVISION SOFTWARE.
5. PROVIDE NPOD TOUCH CONTROL PANEL FOR ON/OFF
PROGRAMMING.